



Power generator

FM 4001

Nr art. 34430

Characteristic

- Voltage stabilization +5 -10 %
- Low level of THD ≤ 6 %
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP IP 23

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	4,2 kW
Nominal power	3,8 kW
Prime current	16,5 A
Engine	Mitsubishi
Model	GB 30 GPN
Capacity	296 cm ³
Cooling	Air
Cylinder	1
Stroke	4
Oil volume	1,0 L
Starting system	Manual
Fuel	Petrol
Fuel tank	6,0 L
Consumption (load 75%)	1,7 L / h
Noise level Lwa	96 dB (A)
Weight	58 kg
Length	650 mm
Width	520 mm
Height	490 mm

Standard equipment

- 2 sockets 230 V 16 A
- Overload protection
- Oil level sensor

Optional and service equipment

- Exhaust hose Nr art. 15876
- Exhaust adapter Nr art. 10113
- Hourmeter Nr art. 23300
- Transportation set Nr art. 24429
- Service kit (air filter, spark plug, engine oil) Nr art. 34789

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/UE**
Low Voltage Directive
- **2014/30/UE**
EC Directive