



Power generator

FV 11001 CRA

Nr art. 28180

Characteristic

- Voltage stabilization $\pm 2\%$
- Low level of THD $< 4\%$
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP IP 23
- Full single phase power output socket 63 Amps
- Autonomy (at 75 % load) 10,2 h
- Low noise level Lwa 94 dB(A)
- Ready for manual and automatic operation

Technical parameters

Frequency	50 Hz
Voltage	230 V
Maximum power	10,5 kW
Nominal power	9,5 kW
Prime current	41,3 A
Engine	Vanguard
Model	3854
Capacity	627 cm ³
Cooling	Air
Cylinder	2
Stroke	4
Oil volume	1,7 L
Starting system	Manual + Electric
Fuel	starter
Fuel tank	Petrol
Consumption (load 75%)	50 L
Noise level Lwa	4,9 L / h 94 dB(A)
Weight	222 kg
Length	1100 mm
Width	600 mm
Height	830 mm

Standard equipment

- AVR
- Socket 230 V 16 A
- Socket 230 V 32 A
- Socket 230 V 63 A
- Overload protection
- Oil pressure sensor
- Silencer with exhaust adapter
- Battery
- Connection for ATS panel
- Hourmeter

Optional and service equipment

- Exhaust hose Nr art. 15876
- Service kit
(air filter, spark plug, engine oil) Nr art. 16579
- ATS panel Nr art. 30310
- Control panel housing Nr art. 28750

Norms and Directives

- **2000/14/WE**
Noise Directive 2005/88/WE
- **2006/42/WE**
Machinery Directive
- **2014/35/WE**
Low Voltage Directive
- **2014/30/WE**
EC Directive