



# Power generator

## FV 11001 TE

Nr art. 28684

### Characteristic

- Voltage stabilization +5 -10 %
- Low level of THD < 4 %
- Shortcut starting current 300 %
- Alternator insulation class H
- Alternator protection IP IP 23
- Full single phase power output socket 63 Amps
- Autonomy (at 75 % load) 9,2 h
- Outdoor operation without enclosure - Noise level Lwa 97 dB(A)
- Frame diameter 38 mm

### Technical parameters

<b>Frequency</b>	<b>50 Hz</b>
<b>Voltage</b>	<b>230 V</b>
<b>Maximum power</b>	<b>11,0 kW</b>
<b>Nominal power</b>	<b>9,9 kW</b>
<b>Prime current</b>	<b>43,0 A</b>
Engine	Vanguard
Model	3854
Capacity	627 cm <sup>3</sup>
Cooling	Air
Cylinder	2
Stroke	4
Oil volume	1,7 L
Starting system	Manual + Electric
Fuel	starter
Fuel tank	Petrol
Consumption (load 75%)	45 L
Noise level Lwa	4,9 L / h 97 dB(A)
Weight	
Length	130 kg
Width	790 mm
Height	580 mm 765 mm

### Standard equipment

- Socket 230 V 16 A
- Socket 230 V 63 A
- Overload protection
- Oil pressure sensor
- Silencer with exhaust adapter
- Battery
- Hourmeter

### Optional and service equipment

- Exhaust hose Nr art. 15876
- Transportation set Nr art. 27874
- Service kit (air filter, spark plug, engine oil) Nr art. 16579

### Norms and Directives

- **2000/14/WE**  
Noise Directive 2005/88/WE
- **2006/42/WE**  
Machinery Directive
- **2014/35/WE**  
Low Voltage Directive
- **2014/30/WE**  
EC Directive