

Fogo[®]



PETROL ENGINE WELDING GENERATOR

POWER GENERATORS

FH 8220 W



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 7,2 kVA / 6,5 kVA |
| Nominal current 3 ~ | 9,4 A |
| Power 1 ~ max / nominal | 3,9 kW / 3,5 kW |
| Nominal current 1 ~ | 15,2 A |
| IP code | IP 23 |
| Voltage regulation | +5 -8 % |
| Engine | Honda GX390 |
| Start mode | Manual |
| Tank | 6,1 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 97 dB(A) |
| Weight | 88 kg |
| Dimensions | 790x580x505 mm |

Item No. 28172

FH 8220 TW



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 7,2 kVA / 6,5 kVA |
| Nominal current 3 ~ | 9,4 A |
| Power 1 ~ max / nominal | 3,9 kW / 3,5 kW |
| Nominal current 1 ~ | 15,2 A |
| IP code | IP 23 |
| Voltage regulation | +5 -8 % |
| Engine | Honda GX390 |
| Start mode | Manual |
| Tank | 45 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 96 dB(A) |
| Weight | 106 kg |
| Dimensions | 790x580x650 mm |

Item No. 28173

FH 8220 TWE



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 7,2 kVA / 6,5 kVA |
| Nominal current 3 ~ | 9,4 A |
| Power 1 ~ max / nominal | 3,9 kW / 3,5 kW |
| Nominal current 1 ~ | 15,2 A |
| IP code | IP 23 |
| Voltage regulation | +5 -8 % |
| Engine | Honda GX390 |
| Start mode | Manual + starter |
| Tank | 45 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 96 dB(A) |
| Weight | 115 kg |
| Dimensions | 790x580x650 mm |

Item No. 28174

FH 9220 W



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 8,7 kVA / 7,8 kVA |
| Nominal current 3 ~ | 11,3 A |
| Power 1 ~ max / nominal | 4,4 kW / 4,0 kW |
| Nominal current 1 ~ | 17,4 A |
| IP code | IP 23 |
| Voltage regulation | ± 4 % |
| Engine | Honda GX390 |
| Start mode | Manual |
| Tank | 6,1 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 97 dB(A) |
| Weight | 98 kg |
| Dimensions | 790x580x505 mm |

Item No. 28601

FH 9220 TW



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 8,7 kVA / 7,8 kVA |
| Nominal current 3 ~ | 11,3 A |
| Power 1 ~ max / nominal | 4,4 kW / 4,0 kW |
| Nominal current 1 ~ | 17,4 A |
| IP code | IP 23 |
| Voltage regulation | ± 4 % |
| Engine | Honda GX390 |
| Start mode | Manual |
| Tank | 45 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 96 dB(A) |
| Weight | 116 kg |
| Dimensions | 790x580x765 mm |

Item No. 28929

FH 9220 TWE



| | |
|--------------------------|-------------------|
| Welding current 35% | 220 A |
| Welding current 60% | 170 A |
| Welding current 100% | 130 A |
| Power 3 ~ max. / nominal | 8,7 kVA / 7,8 kVA |
| Nominal current 3 ~ | 11,3 A |
| Power 1 ~ max / nominal | 4,4 kW / 4,0 kW |
| Nominal current 1 ~ | 17,4 A |
| IP code | IP 23 |
| Voltage regulation | ± 4 % |
| Engine | Honda GX390 |
| Start mode | Manual |
| Tank | 45 L |
| Consumption (75% power) | 2,7 L / h |
| Noise level (LWA) | 96 dB(A) |
| Weight | 126 kg |
| Dimensions | 790x580x765 mm |

Item No. 28930

Three-phase 400 / 230 V 50 Hz
Power up to 11,0 kVA (cos φ 0,8)
Welding current up to 300 A

FV 11300 TWE



| | |
|--------------------------|---------------------|
| Welding current 35% | 300 A |
| Welding current 60% | 240 A |
| Welding current 100% | 185 A |
| Power 3 ~ max. / nominal | 11,0 kVA / 10,0 kVA |
| Nominal current 3 ~ | 14,5 A |
| Power 1 ~ max. / nominal | 4,4 kW / 4,0 kW |
| Nominal current 1 ~ | 17,4 A |
| IP code | IP 23 |
| Voltage regulation | ± 4 % |
| Engine | Vanguard 21HP |
| Start mode | Manual + starter |
| Tank | 45 L |
| Consumption (75% power) | 4,9 L / h |
| Noise level (LWA) | 97 dB(A) |
| Weight | 157 kg |
| Dimensions | 900x580x800 mm |

Item No. 28196

Welding cables 3 mb - 35 mm²



| Models | Item No. |
|--|----------|
| FH 8220 W, FH 8220 TW FH 8220 TWE, FH 9220 W FH 9220 TW, FH 9220 TWE | 14110 |

Welding cables 10 mb - 35 mm²



| Models | Item No. |
|--|----------|
| FH 8220 W, FH 8220 TW FH 8220 TWE, FH 9220 W FH 9220 TW, FH 9220 TWE | 14113 |

Welding cables 6,8 mb - 50 mm²



| Models | Item No. |
|--------------|----------|
| FV 11300 TWE | 14111 |

Welding cables 10 mb - 50 mm²



| Models | Item No. |
|--------------|----------|
| FV 11300 TWE | 14114 |

Exhaust hose



| Models | Item No. |
|--|----------|
| FH 8220 W, FH 8220 TW FH 8220 TWE, FH 9220 W FH 9220 TW, FH 9220 TWE FV 11300 TWE | 15876 |

Exhaust hose connection



| Models | Item No. |
|--|-------------------|
| FH 8220 W, FH 9220 W FH 8220 TW, FH 8220 TWE FH 9220 TW, FH 9220 TWE FV 11300 TWE | 10118 STANDARD |

Hour meter



| Models | Item No. |
|--|----------|
| FH 8220 W, FH 8220 TW FH 8220 TWE, FH 9220 W FH 9220 TW, FH 9220 TWE FV 11300 TWE | 23300 |

Transport kit



| Models | Item No. |
|--|----------------|
| FH 8220 W, FH 9220 W FH 8220 TW, FH 8220 TWE FH 9220 TW, FH 9220 TWE FV 11300 TWE | 28807 28784 |

Service Kit



| Models | Item No. |
|--|-------------------------|
| FH 8220 W, FH 9220 W FH 8220 TW, FH 8220 TWE FH 9220 TW, FH 9220 TWE FV 11300 TWE | 16582 23294 16579 |



www.fogo.pl

2000/14/WE Noise Directive 2005/88/WE
2006/42/WE Machinery Directive
2014/35/WE Low Voltage Directive
2014/30/WE EC Directivej

We reserve the right to change specifications and product designs presented in this publication.